



HOW TO USE

ACID Magic®

ACID Magic® The User Friendly Muriatic Acid!™

ADVANCED FORMULA

READ INSTRUCTIONS IN THEIR ENTIRETY BEFORE PROCEEDING.

ACID Magic should not be used to aid or effect any pool disinfectant product or other water modifier.

READY-MIX CONCRETE TRUCK AND TOOL CLEANING

ACID Magic is the best way to remove stubborn rust, hard water and mineral deposits from a variety of surfaces. It can be used to remove calcium and other stains that build-up on steel and iron parts, most plastics, painted block and metal, and other non-porous, non-metal surfaces.



DILUTION & APPLICATION:

MIXER EXTERIOR:

Spray or brush on with natural bristle brush, let dwell for 5 minutes, agitate, and rinse. Repeat as necessary.

- New, reconditioned, or well maintained trucks:
Dilute 1 part ACID Magic to 6 parts water
- Moderate concretions and regularly washed trucks:
Dilute 1 part ACID Magic to 4 parts water
- Heavy build-up and seldom washed trucks:
Dilute 1 part ACID Magic to 2 parts water
- Extra heavy build-up and rarely washed trucks:
Dilute 1 part ACID Magic to 1 part water

MIXER INTERIOR:

Apply a generous amount of solution into the mixer. Allow mixer to clean itself by running and agitating concretion. Flush with plenty of water. Repeat as necessary.

- Dilute 1 part ACID Magic to 10 parts water.

TOOLS & MACHINERY:

Let dwell between 30-40 minutes. Rinse tool with water. Seal the tool with a lubricating metal protecting agent to prevent corrosion.

- Variable dilution 1:10 up to 1:1, the dilution depends on the amount of rust, plaster, or concrete on the tool.
- For heavier rust or concretion, use 1:1 to maximize effectiveness.

PRECAUTIONS:

- While using ACID Magic, protective eyewear and gloves are always required.
- **When diluting, ALWAYS add the ACID Magic to water, NOT water to the ACID Magic. This eliminates the potential of an unwanted reaction that may cause dangerous splashing to occur.**
- **Do not apply to dry surfaces.** Always wet surfaces prior to application, including adjoining areas, in case of accidental spillage.
- **Do not allow the surface to dry with ACID Magic solution on it.**
- Avoid contact with vegetation. Excess solution should be diverted away from grass, trees and shrubs. Should accidental contact with vegetation occur, flush with large amounts of water.
- Discharge permit may be necessary. Dispose of ACID Magic according to all local, state and federal regulations.
- Test surface to be cleaned with various dilutions for safety and effectiveness.

MicroCare • 6120 East 58th Avenue, Commerce City, CO 80022 • (800) 843-3343 • AcidMagic.com

© 2022 MicroCare. All Rights Reserved. "MicroCare", "Acid Magic" and Acid Magic Logo are trademarks or registered trademarks of MicroCare, LLC. The information set forth herein is based on data believed to be reliable. MicroCare makes no warranties express or implied as to its accuracy and assumes no liability arising out of its use by others. This publication is not to be taken as a license to operate under, nor infringe upon, any patents not herein expressly described.

AM HTU 7: Truck and Tool • Rev. 22355